CcspWiFiAgent support

- Introduction
- Branch
- Build Instructions
 - RPI4 32bitRPI4 64bit
- Supported devices
- Sanity Testing
- References
- EPIC/User Stories

Introduction

The scope of this activity is to migrate from existing OneWiFi component to CcspWiFiAgent component in RDK-B Reference platform. As some of the platforms like xb3 are still using CcspWiFiAgent component instead of Onewifi.

Branch

https://code.rdkcentral.com/r/plugins/gitiles/rdkb/components/opensource/ccsp/CcspWifiAgent/+/refs/heads/main

Build Instructions

Step 1: Disable OneWiFi distro feature from /meta-cmf-raspberrypi/conf/distro/include/rdk-rpi.inc after repo sync j nproc --no-clone-bundle.

```
# OneWifi feature
-DISTRO_FEATURES_append_broadband = " OneWifi"
+#DISTRO_FEATURES_append_broadband = " OneWifi"
```

Step 2: After disabling the feature, MACHINE command and bitbake rdk-generic-broadband-image

RPI4 32bit

```
RPI4 32bit

mkdir dir
cd dir

rdkcentral.com

sync

source
```

Reference link: RPI 4B Model Reference Platform

RPI4 64bit

```
RPI4 64bit

mkdir dir
cd dir
rdkcentral.com
sync source
```

Reference link: RPI 4B Model Reference Platform with 64bit Arch

Supported devices

Sanity Testing



References

EPIC/User Stories

